



Length	cable material Length	Final Length
1.00 m	950+10/-0mm	1000±10mm
1.50 m	1450+15/-0mm	1500±15mm
1.70 m	1650+15/-0mm	1700±15mm
1.80 m	1750+20/-0mm	1800±20mm
2.00 m	1950+20/-0mm	2000±20mm
2.115 m	2065+20/-0mm	2115±20/0mm
3.00 m	2950+30/-0mm	3000±30mm
5.00 m	4950+40/-0mm	5000±40mm

4	Inner Mold	PE-0001	LDPE料 (RoHS)-PE101	3.00g
3	S. R	PVC-0001	60P PVC Black	2.70g
	线夹	OR-0079	DP 32#线夹	2 Pcs
2	upside case	SL-BK0055	DP (M) Black	2 Pcs
	Downside case	SL-BK0054	DP (M) Black	2 Pcs
	Connector	CN-G0010	DP (M) PCB Gold plated	2 Pcs
1	cable spec.	DP1-55-3207	UL20276 (32AWG*1P+D+AL/MY)*5C+32AWG*5C/MY/AL+BRAID, JACKET PVC BLACK. OD=5.5±0.20mm	1 Pcs
NO.	material name			Doses

(DWG NO)	XY-A0052	单位(UNIT)	MM
(REV)	A4	比例(SCALE)	任意
(PAGE)	1/1		
(DESIGN)	Dean	<small>SIMENSIONS ARE IN MILLIMETERS TOLERANCES</small> LINEAR: X ± 1.0 XX ± 0.5 XXX ± 0.15 XXXX ± 0.05 ANGULAR: ± 0.5°	
(CHECKED)			
(APPROVED)			