

New Product **PU-514L-KIT**

v1.4 HDMI over Single CAT5e/6/7 HDBaseT™ LITE with 2-Way IR (up to 60m)



The PU-514-KIT allows uncompressed HDMI, and 2-way IR signals to be transmitted over a Single CAT5e/6/7 cable to distances of up to 60m.

FEATURES

- HDMI 1.4 with 3D, 4Kx2K support, HDCP and DVI compliant
- Supports HDMI 1.4 (including HDCP) over a single CAT5e/6/7 up to 60m
- Complies with HDBaseT™- Lite specifications
- Full HD resolution support (1080p@60Hz/36-bit), 3D over 60m, 4Kx2K over 40m and PC resolution support (VGA to WUXGA) over CAT5e/6 cable
- HDMI input up to 15m with 8-bit deep colour, or 10m with 12-bit deep colour
- Supports HDMI output up to 15m with 8/12-bit deep colour
- Supports 2-way IR
- Supports High Definition LPCM 7.1CH, Dolby TrueHD, Dolby Digital Plus and DTS-HD Master Audio transmission

SPECIFICATIONS

PU-514L-TX

Inputs	1x HDMI (1x HDMI Uncompressed AV and Data), 1x 3.5mm Stereo mini-jack (1x Infra Red Receiver)
Outputs	1x RJ45 (1x HDMI & Propriety Data), 1x 3.5mm Stereo mini-jack (1x Infra Red Emitter)
Power:	5V/2.6A US/EU standards, CE/FCC/UL certified)
Dimensions:	55mm (W) x 83mm (D) x 22mm (H)
Net Weight:	60g

PU-514L-RX

Inputs:	1x RJ45 (1x HDMI & Propriety Data), 1x 3.5mm Stereo mini-jack (1x Infra, Red Receiver)
Outputs:	1x HDMI (1x HDMI Uncompressed AV and Data), 1x 3.5mm Stereo mini-jack (1x Infra Red Emitter)
Power:	5V/2.6A US/EU standards, CE/FCC/UL certified)
Dimensions:	55mm (W) x 52mm (D) x 22mm (H)
Net Weight:	60g
Gross Weight:	280g
Packaging:	Boxed

