

		IPPC-7	IPPC-10	IPPC-10 HD	IPPC-15	IPPC-22	IPPC-24	IPPC-27	IPPC-32
Panel	Size	7"	10.1"	10.1"	15.6"	21.5"	23.6"	27"	31.5"
	Type	TFT LCD	TFT LCD	TFT LCD IPS	TFT LCD IPS	TFT LCD IPS	TFT LCD IPS	TFT LCD IPS	TFT LCD IPS
	Resolution	1024 x 600	1024 x 600	1280 x 800	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
	Aspect Ratio	17:10 wide	17:10 wide	16:10 wide	16:9 wide	16:9 wide	16:9 wide	16:9 wide	16:9 wide
	Backlight	LED Side-light type	LED Side-light type	LED Side-light type	LED Side-light type	LED Side-light type	LED Side-light type	LED Side-light type	LED Side-light type
	Brightness	240 cd/m ²	450 cd/m ²	500 cd/m ²	300 cd/m ²	250 cd/m ²	250 cd/m ²	300 cd/m ²	400 cd/m ²
	Viewing Angle	H 140° / V 130°	H 140° / V 130°	H 160° / V 160°	H 170° / V 170°	H 178° / V 178°	H 178° / V 178°	H 170° / V 160°	H 178° / V 178°
	Contrast Ratio	600 : 1	600 : 1	600 : 1	800 : 1	1000 : 1	1000 : 1	1000 : 1	1000 : 1
	Touch Type	5 point touch projected capacitive	5 point touch projected capacitive	5 point touch projected capacitive	10 point touch projected capacitive	10 point touch projected capacitive	10 point touch projected capacitive	10 point touch projected capacitive	10 point touch projected capacitive
System (SOC)	CPU *	Intel Braswell N3160 Quad Core	Intel Braswell N3160 Quad Core	Intel Braswell N3160 Quad Core	Intel Braswell N3160 Quad Core	Intel Braswell N3160 Quad Core	Intel Braswell N3160 Quad Core	Intel Braswell N3160 Quad Core	Intel Braswell N3160 Quad Core
	GPU	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics
	Cooling	Fanless	Fanless	Fanless	Fanless	Fanless	Fanless	Fanless	Fanless
	System Memory	4 GB DDR3L 1600	4 GB DDR3L 1600	4 GB DDR3L 1600	4 GB DDR3L 1600	4 GB DDR3L 1600	4 GB DDR3L 1600	4 GB DDR3L 1600	4 GB DDR3L 1600
	Internal Storage	64 GB M.2 SSD TLC	64 GB M.2 SSD TLC	64 GB M.2 SSD TLC	64 GB M.2 SSD TLC	64 GB M.2 SSD TLC	64 GB M.2 SSD TLC	64 GB M.2 SSD TLC	64 GB M.2 SSD TLC
	Storage Socket 2	SD Card Slot (internal)	SD Card Slot (internal)	SD Card Slot (internal)	SD-Card Slot (door)	SD Card Slot (internal)	SD Card Slot (internal)	SD Card Slot (internal)	SD Card Slot (internal)
	OS	Windows 8 / 10 / Linux	Windows 8 / 10 / Linux	Windows 8 / 10 / Linux	Windows 8 / 10 / Linux	Windows 8 / 10 / Linux	Windows 8 / 10 / Linux	Windows 8 / 10 / Linux	Windows 8 / 10 / Linux
	I/O Ports	Micro-USB / USB / Mini-HDMI / GPIO Port / 3.5mm audio-out / RJ45 / POGO-Connector / 12VDC-IN	Micro-USB / USB / Mini-HDMI / GPIO Port / 3.5mm audio-out / RJ45 / POGO-Connector / 12VDC-IN	USB 3.0 / USB 2.0 / GPIO Port / 3.5mm audio out / RJ45 / POGO-Connector / 12VDC-IN	Micro USB 2.0 / USB 3.0 / USB 2.0 / Mini-HDMI / GPIO Port / Combo Jack / SPDIF / RJ45 / POGO-Connector / 12VDC-IN	Micro USB 2.0 / USB 3.0 / USB 2.0 / GPIO Port / Combo Jack / SPDIF / RJ45 / 12VDC-IN	Micro USB 2.0 / USB 3.0 / USB 2.0 / GPIO Port / Combo Jack / SPDIF / RJ45 / 12VDC-IN	Micro USB 2.0 / USB 3.0 / USB 2.0 / GPIO Port / Combo Jack / SPDIF / RJ45 / 12VDC-IN	Micro USB 2.0 / USB 3.0 / USB 2.0 / GPIO Port / Combo Jack / SPDIF / RJ45 / 12VDC-IN
	Network LAN RJ45	10/100/1000 Mbps LAN	10/100/1000 Mbps LAN	10/100/1000 Mbps LAN	10/100/1000 Mbps LAN	10/100/1000 Mbps LAN	10/100/1000 Mbps LAN	10/100/1000 Mbps LAN	10/100/1000 Mbps LAN
	WiFi / Bluetooth	802.11 b/g/n SIP wireless module	802.11 b/g/n SIP wireless module	802.11 b/g/n SIP wireless module	802.11 b/g/n SIP wireless module	802.11 b/g/n SIP wireless module	802.11 b/g/n SIP wireless module	802.11 b/g/n SIP wireless module	802.11 b/g/n SIP wireless module
(PoE) Power over Ethernet	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Physical	Housing	Plastic Front / Metal Backside	Plastic	Plastic	Plastic	Metal	Metal	Metal	Metal
	Color	Black	Black	Black	Black	Black	Black	Black	Black
	Speakers	2 x 2W	2 x 2W	2 x 2W	2 x 2W	2 x 2W	2 x 2W	2 x 2W	2 x 2W
	Audio Jack Output 3.5mm	OPTIONAL	OPTIONAL	YES	YES	YES	YES	YES	YES
	Weight	440g / 500g	615g	600g / 610g	1400g	7000g	7500g	8300g	10450g
	Dimensions	188 x 120 x 25 mm	260 x 163 x 25 mm	252 x 178 x 24 mm	387.3 x 240.3 x 27.2 mm	536 x 329 x 43 mm	576 x 345 x 43 mm	650 x 390 x 43 mm	769 x 471 x 49 mm
	Mounting / VESA	VESA 75*48	VESA 75	VESA 75	VESA 100	VESA 100	VESA 100	VESA 100 / 200	VESA 200
	Power Supply	12V / 2A	12V / 2A	12V / 2A	12V / 5A	12V / 5A	12V / 5A	12V / 5A	12V / 5A
Power Usage	9 Watt	9 Watt	10.32 Watt / 25.6 Watt	10.32 Watt / 25.6 Watt	10.32 Watt / 25.6 Watt	10.32 Watt / 25.6 Watt	10.32 Watt / 25.6 Watt	10.32 Watt / 25.6 Watt	
Other	Working Temp	-10 ~ 50 degrees C	-10 ~ 50 degrees C	-10 ~ 50 degrees C	0 ~ 40 degrees C	0 ~ 40 degrees C	0 ~ 40 degrees C	0 ~ 40 degrees C	0 ~ 40 degrees C
	Standard Warranty	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years
	Certifications	FCC, CE, & RoHS	FCC, CE, & RoHS	FCC, CE, & RoHS	FCC, CE, & RoHS	FCC, CE, & RoHS	FCC, CE, & RoHS	FCC, CE, & RoHS	FCC, CE, & RoHS