

MODEL	LS425	LS445	HD225	HD1025	XD235	XD1035	XT245	XT1145	XT2145	XC2055	XC4055
BrightSign Mobile USB modem	X	X		X		X		X	X	X	X
CBL-USBC to USBA and 3.5mm Serial	X	X				X		X	X	X	X
GP800-C: USB C to GPIO 12-pin Cable Kit	X	X				X		X	X	X	X
SOFTWARE & SERVICES											
BrightSignOS	X	X	X	X	X	X	X	X	X	X	X
Free BrightAuthor:connected or BrightAuthor software	X	X	X	X	X	X	X	X	X	X	X
Free Control Cloud Subscription	X	X	X	X	X	X	X	X	X	X	X
Optional BSN.cloud Paid Subscription	X	X	X	X	X	X	X	X	X	X	X
Optional BrightSign Mobile Service	X	X		X		X		X	X	X	X
MISCELLANEOUS											
Anodized aluminum enclosure for extended operating temperatures			X	X	X	X	X	X	X		
Dimensions	126.6 x 141.84 x 19.41 mm (WxDxH)		205 x 185.9 x 19.2 mm (WxDxH)		205 x 185.9 x 19.2 mm (WxDxH)		238.62 x 185.90 x 19.19 (WxDxH)			253.2 x 232.12 x 48mm (WxDxH)	
Shipping Weight	TBD	TBD	1.3 kg	1.3 kg	1.3 kg	1.3 kg	TBD	TBD	TBD	3 kg	3 kg
Player Weight	0.18 kg	0.18 kg	0.59 kg	0.59 kg	0.59 kg	0.59 kg	0.68 kg	0.68 kg	0.68 kg	1.41 kg	1.41 kg
Power Supply	12V / 3A	12V / 3A	12V / 3A	12V / 3A	12V / 3A	12V / 3A	12V / 3A	12V / 3A	12V / 3A	19V / 4.7A	19V / 4.7A
Multi-Country Power & Regulatory Approvals	X	X	X	X	X	X	X	X	X	X	X
Built-in Wall Mounting Brackets	X	X	X	X	X	X	X	X	X	X	X
1 year warranty, parts and labor*	X	X	X	X	X	X	X	X	X	X	X

*2 year warranty, parts and labor, for units shipped from an EU or UK distribution center and to an EU or UK address.